

## Technical Information

### STR700 SmartLine Remote Diaphragm Seals Specification 34-ST-03-104



#### Introduction

Part of the SmartLine® family of products, the STR700 is suitable for monitoring, control and data acquisition. STR700 products feature piezoresistive sensor technology combining pressure sensing with on chip temperature compensation capabilities providing high accuracy, stability and performance over a wide range of application pressures and temperatures. The SmartLine family is also fully tested and compliant with Experion® PKS providing the highest level of compatibility assurance and integration capabilities. SmartLine easily meets the most demanding application needs for pressure measurement applications



#### Best in Class Transmitter Features:

- Accuracies up to 0.075% standard
- Automatic static pressure & temperature compensation
- Rangeability up to 100:1
- Local display capabilities
- External zero, span, & configuration capability
- Polarity insensitive electrical connections
- Comprehensive on-board diagnostic capabilities
- Integral Dual Seal design for highest safety based on ANSI/NFPA 70-202 and ANSI/ISA 12.27.0
- World class overpressure protection
- Full compliance to SIL 2/3 requirements.
- Modular design characteristics
- Available with 15 year warranty

Figure 1 – STR700 Remote Diaphragm Seal Unit

#### Typical Diaphragm Seal applications

- High Process Temperatures
- Viscous or Suspended Solids
- Highly Corrosive Process Materials
- Sanitary Applications
- Applications with Hydrogen Permeation Possibilities
- Level Applications with Maintenance Intensive Wet Legs
- Applications requiring remote Transmitter Mounting
- Tank Applications with Density or Interface Measurements

#### Communications/Output Options:

- Honeywell Digitally Enhanced (DE)
- HART® (version 7.0)
- FOUNDATION™ Fieldbus

All transmitters are available with the above listed communications protocols.

#### Remote Seal/Transmitter Span & Range Limits:

Model	psid (bar)	psid (bar)	psid (bar)	psid (bar)
STR73D	100 (7.0)	-100 (-7.0)	100 (7.0)	1 (0.07)
Model	psig (bar)	psig (bar)	psig (bar)	psig (bar)
STR74G	500 (35.0)	-500 (-35.0)	500 (35.0)	5 (035)

По вопросам продаж и поддержки обращайтесь:

Астана +7(7172)727-132, Волгоград (844)278-03-48, Воронеж (473)204-51-73, Екатеринбург (343)384-55-89, Казань (843)206-01-48, Краснодар (861)203-40-90, Красноярск (391)204-63-61, Москва (495)268-04-70, Нижний Новгород (831)429-08-12, Новосибирск (383)227-86-73, Ростов-на-Дону (863)308-18-15, Самара (846)206-03-16, Санкт-Петербург (812)309-46-40, Саратов (845)249-38-78, Уфа (347)229-48-12

Единый адрес: hwn@nt-rt.ru  
www.honeywell.nt-rt.ru

## Description

The SmartLine family pressure transmitters are designed around a high performance piezo-resistive sensor. This one sensor actually integrates multiple sensors linking process pressure measurement with on-board static pressure (DP Models) and temperature compensation measurements. This level of performance allows the ST 700 to replace most competitive transmitters available today.

## Indication/Display Option

The ST 700 modular design accommodates a basic alphanumeric LCD display.

### Basic Alphanumeric LCD Display Features

- Modular (may be added or removed in the field)
- 0, 90, 180, & 270 degree position adjustments
- Pa, KPa, MPa, KGcm<sup>2</sup>, Torr, ATM, i4H<sub>2</sub>O, mH<sub>2</sub>O, bar, mbar, inH<sub>2</sub>O, inHG, FTH<sub>2</sub>O, mmH<sub>2</sub>O, mm HG, & psi measurement units
- 2 Lines 16 Characters (4.13H x 1.83W mm)
- Square root output indication ( $\sqrt{\quad}$ )

## Diagnostics

SmartLine transmitters all offer digitally accessible diagnostics which aid in providing advanced warning of possible failure events minimizing unplanned shutdowns, providing **lower overall operational costs**

## Configuration Tools

### Integral Three Button Configuration Option

Suitable for all electrical and environmental requirements, SmartLine offers the ability to configure the transmitter and display via three externally accessible buttons when a display option is selected. Zero/span capabilities are also optionally available via these buttons with or without selection of the display option.

### Hand Held Configuration

SmartLine transmitters feature two-way communication and configuration capability between the operator and the transmitter. This is accomplished via Honeywell's field-rated Multiple Communication Configurator (MCT202). The MCT202 is capable of field configuring DE and HART Devices and can also be ordered for use in intrinsically safe environments. All Honeywell transmitters are designed and tested for compliance with the offered communication protocols and are designed to operate with any properly validated hand held configuration device.

## Personal Computer Configuration

Honeywell's SCT 3000 Configuration Toolkit provides an easy way to configure Digitally Enhanced (DE) instruments using a personal computer as the configuration interface. Field Device Manager (FDM) Software and FDM Express are also available for managing HART & Fieldbus device configurations.

## System Integration

- SmartLine communications protocols all meet the most current published standards for HART/DE/Fieldbus.
- Integration with Honeywell's Experion PKS offers the following unique advantages.
  - Tamper reporting
  - FDM Plant Area Views with Health summaries
  - All ST 700 units are Experion tested to provide the highest level of compatibility assurance

## Modular Design

To help contain maintenance & inventory costs, all ST 700 transmitters are modular in design supporting the user's ability to replace meter bodies, add indicators or change electronic modules without affecting overall performance or approval body certifications. Each meter body is uniquely characterized to provide in-tolerance performance over a wide range of application variations in temperature and pressure and due to the Honeywell advanced interface, electronic modules may be swapped with any electronics module without losing in-tolerance performance characteristics.

### Modular Features

- Meter body replacement
- Exchange/replace electronics/comms modules\*
- Add or remove integral indicator\*
- Add or remove lightning protection (terminal connection)\*

\* Field replaceable in all electrical environments (including IS) except flameproof without violating agency approvals.

With no performance effects, Honeywell's unique modularity results in **lower inventory needs and lower overall operating costs**.

## Performance Specifications<sup>1</sup>

**Reference Accuracy<sup>2</sup>** (conformance to +/-3 Sigma)

Model	URL	LRL	Min Span	Maximum Turndown Ratio	Reference Accuracy <sup>1</sup> (% Span)
STR73D	100 psid/7.0 bar	-100 psi/-7.0bar	9 psi/.07bar	100:1	0.075
STR74G	500 psi/35 bar	-14.7 psi/-1.0 bar	5 psi/.035 bar	100:1	0.075

Zero and span may be set anywhere within the listed (URL/LRL) range limits

		Accuracy <sup>1</sup> (% of Span)				Temperature Effect * (% Span/50°F)		
Model	URL	Turn down greater than	A	B	C psi(bar)	D	E	F psi(bar)
STR73D	100 psi/7.0 bar	27.7:1	0.0250	0.050	3.61 (0.249)	0.028	1.200	7.2 (0.50)
STR74G	500 psig/35 bar	25:1	0.0250	0.050	20 (1.4)			
		Turn Down Effect $\pm \left[ A + B \left( \frac{C}{\text{Span}} \right) \right]$ % Span				Temp Effect $\pm \left[ D + E \left( \frac{F}{\text{Span}} \right) \right]$ % Span per 28°C (50°F)		

**Accuracy at Specified Span, Temperature and Static Pressure:** (conformance to +/-3 Sigma)

**Total Performance (% of Span):**

$$\text{Total Performance} = \pm \sqrt{(\text{Accuracy})^2 + (\text{Temp Effect})^2}$$

**Total Performance Examples:** (5:1 Turndown, up to 50 °F shift)

STR73D @ 20 psid: 1.03% of span

**Typical Calibration Frequency:**

Calibration verification is recommended every four (4) years

**Notes:**

1. Terminal Based Accuracy – Includes combined effects of linearity, hysteresis, and repeatability. Analog output adds 0.005% of span.
2. For zero based spans and reference conditions of 25°C (77°F), 0 psig static pressure, 10 to 55% R.H. and 316Stainless Steel barrier diaphragms
3. Specification applies to transmitter with 2 seals. Apply a factor of 1.5 for temperature effect of capillary lengths greater than 10 feet.

**Operating Conditions – All Models**

Parameter	Reference Condition (at zero static)		Rated Condition		Operative Limits		Transportation and Storage																												
	°C	°F	°C	°F	°C	°F	°C	°F																											
Ambient Temperature <sup>1</sup>	25±1	77±2	-	-	-	-	-55 to 90	-67 to 194																											
Humidity %RH	10 to 55		0 to 100		0 to 100		0 to 100																												
Vacuum Region, Minimum Pressure mmHg absolute	Atmospheric (See Figure 4 for vacuum limitation)																																		
Supply Voltage, Current, and Load Resistance	10.8 to 42.4 Vdc at terminals (IS versions limited to 30 Vdc) 0 to 1,440 ohms (as shown in Figure 2)																																		
Maximum Allowable Working Pressure (MAWP) <sup>4</sup> <small>(ST 700 products are rated to Maximum Allowable Working Pressure. MAWP depends on Approval Agency and transmitter materials of construction.)</small>	MAWP is minimum of Body Rating or Seal Rating (See Model Selection Guide for Seal MAWP) <table border="0"> <tr> <td><b>Body</b></td> <td><b>MAWP</b></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>STR73D</td> <td>750 psig (51.7 bar)</td> <td>Bolted</td> <td>Process</td> <td>Heads</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>STR74G</td> <td>500 psig (35 bar)</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>								<b>Body</b>	<b>MAWP</b>								STR73D	750 psig (51.7 bar)	Bolted	Process	Heads					STR74G	500 psig (35 bar)							
<b>Body</b>	<b>MAWP</b>																																		
STR73D	750 psig (51.7 bar)	Bolted	Process	Heads																															
STR74G	500 psig (35 bar)																																		

<sup>1</sup> Ambient Temperature Limit is a function of Process Interface Temperature. (See Figures 3 & 4)  
 LCD Display operating temperature -20°C to +70°C . Storage temperature -30°C to 80°C

<sup>4</sup> Consult factory for MAWP of ST 700 transmitters with CRN approval.




Figure 2 - Supply voltage and loop resistance




Figure 3 - Ambient temperature Limits





Figure 4 - STR700 Remote Seals operable limits for pressure vs. temperature



**Minimum recommended span for STR73D Transmitter with two Remote Seals**

Diaphragm Size	Capillary						Capillary Length Maximum
	5"	10"	15"	20"	30"	35"	
2.4	200 iwc						5'
2.9	100 iwc	125 iwc	150 iwc	175 iwc			20'
3.5	16 iwc	20 iwc	24 iwc	28 iwc	36 iwc	40 iwc	35'
4.1	12 iwc	15 iwc	18 iwc	21 iwc	27 iwc	30 iwc	35'


**Minimum recommended span for STR73D Transmitter with one Remote Seal**

Diaphragm Size	Direct Mount	Capillary						Capillary Length
		5"	10"	15"	20"	30"	35"	
2.4	20 psig	30 psig						5'
2.9	10 psig	15 psig	20 psig	25 psig	30 psig			20'
3.5	50 iwc	80 iwc	100 iwc	120 iwc	140 iwc	180 iwc	200 iwc	35'
4.1	40 iwc	60 iwc	80 iwc	100 iwc	120 iwc	160 iwc	180 iwc	35'

**Minimum recommended span for STR74G Transmitter with one Remote Seal**

Diaphragm Size	Direct Mount	Capillary						Capillary Length
		5"	10"	15"	20"	30"	35"	
2.0	25 psig	30 psig	40 psig					15'
2.4	10 psig	15 psig	20 psig	25 psig	30 psig	40 psig	50 psig	35'
2.9	8 psig	9 psig	10 psig	11 psig	12 psig	14 psig	15 psig	35'
3.5	5 psig	5 psig	5 psig	120 psig	140 psig	180 psig	200 psig	35'
4.1	5 psig	5 psig	5 psig	100 psig	120 psig	160 psig	180 psig	35'

**Figure 5– Typical Maximum capillary length and diaphragm size chart**





NOTE: Lower flange seal should not be mounted over 22 feet below or above the transmitter for silicone fill fluid (11 feet for CTFE fill fluid) with tank at one atmosphere. The combination of tank vacuum and high pressure capillary head effect should not exceed 9 psi vacuum (300 mmHg absolute).

Consult Honeywell for installation of STR73D.

**Figure 6 - STR700 transmitter with remote diaphragm seals shown mounted on a tank**



Reference Dimensions Horizontal Mounting





Reference Dimensions Horizontal Mounting (cont'd)





Figure 7 — Approximate horizontal mounting dimensions for Remote Seal Transmitter

Reference Dimensions Vertical Mounting



Reference Dimensions Vertical Mounting (cont'd)






Figure 8 — Approximate vertical mounting dimensions for Remote Seal Transmitter

**Reference Dimensions (cont'd)**


**Flush Flanged Seal Dimensions**

Type	ANSI/DIN Rating	Flange Material	Wetted Materials		Construction See figura	↔	
			Diaphragm	Body		A	B
Flush Flanged Seal	3" Class 150#	CS	SS	SS	D	7.5	1.37
			Hastelloy C	SS	C		
			Hastelloy C	Hastelloy C	D		
			Monel	Monel	D		
		Tantalum	SS	C			
		SS	SS	N/A	B	7.90	0.94
			Hastelloy C	SS	A		
			Hastelloy C	Hastelloy C	D		
	Monel		Monel	D			
	Tantalum	SS	C				
	3" Class 300#	CS	SS	SS	D	8.25	1.58
			Hastelloy C	SS	C		
			Hastelloy C	Hastelloy C	D		
			Monel	Monel	D		
		Tantalum	SS	C			
		SS	SS	N/A	B	8.25	1.12
			Hastelloy C	SS	A		
			Hastelloy C	Hastelloy C	D		
	Monel		Monel	D			
	Tantalum	SS	C				
3" Class 600#	CS	SS	SS	D	8.25	1.75	
		Hastelloy C	SS	C			
		Hastelloy C	Hastelloy C	D			
		Monel	Monel	D			
	Tantalum	SS	C				
	SS	SS	N/A	B	8.25	1.5	
		Hastelloy C	SS	A			
		Hastelloy C	Hastelloy C	D			
Monel		Monel	D				
Tantalum	SS	C					
DN20-PN40	CS	SS	SS	D	7.87	1.32	
		Hastelloy C	SS	C			
		Hastelloy C	Hastelloy C	D			
		Monel	Monel	D			
	Tantalum	SS	C				
	SS	SS	N/A	B	7.87	0.94	
		Hastelloy C	SS	A			
		Hastelloy C	Hastelloy C	D			
Monel		Monel	D				
Tantalum	SS	C					




**Configuration "HS"**

**Figure A**




**Configuration "HT"**

**Figure B**



**Configuration "IS"**

**Figure C**



**Configuration "IT"**

**Figure D**


**Figure 9 - Seal Dimensions (Flush Flanged)**

## Reference Dimensions (cont'd)


### Flush Flanged Seal with Lower

Type	ANSI/DIN Rating	Size	Dimension	2.4" Diaph. Dia. (in.)	2.9" Diaph. Dia. (in.)	4.1" Diaph. Dia. (in.)
Flush Flanged Seal with Lower	Class 150#	1/2"	A	3.50	4.00	5.25
			B0	1.72	1.72	1.84
			B1	1.72	1.72	1.84
			B2	2.22	2.22	2.34
		1"	B0	4.25	4.00	5.25
			B2	1.12	1.72	1.84
		1-1/2"	B0	1.62	1.72	1.84
			B1	1.99	1.72	2.34
			B2	5.00	5.00	5.25
			B0	2.50	2.50	1.78
		2"	B1	3.00	3.00	2.12
			B2	3.50	3.40	2.12
	A		6.00	6.00	6.00	
	B0		2.50	2.50	2.12	
	3"	B1	3.00	3.00	2.12	
		B2	3.50	3.40	2.12	
		A	7.50	7.50	7.50	
		B0	2.58	2.88	2.60	
	Class 300#	1"	B1	2.88	2.88	3.00
			B2	3.50	3.40	3.40
A			4.88	4.00	5.25	
B0			2.50	1.72	1.88	
1-1/2"		B1	3.00	1.72	2.12	
		B2	3.50	2.22	2.12	
		A	6.12	6.12	6.25	
		B0	2.50	2.50	2.12	
2"		B1	3.00	3.00	2.12	
		B2	3.50	3.40	2.12	
		A	6.50	6.50	6.50	
		B0	2.50	2.50	2.70	
3"	B1	3.00	3.00	3.00		
	B2	3.50	3.40	3.50		
	A	8.25	8.25	8.25		
	B0	3.48	3.48	3.20		
Class 600#	1"	B1	3.48	3.48	3.60	
		B2	4.10	4.00	4.00	
		A	4.88	4.50	5.25	
		B0	2.50	2.15	2.26	
	1-1/2"	B1	3.00	2.15	2.26	
		B2	3.50	2.40	2.50	
		A	6.12	6.12	5.25	
		B0	2.50	1.53	2.50	
	2"	B1	3.00	2.09	3.00	
		B2	3.50	2.49	3.50	
		A	6.50	6.50	6.50	
		B0	3.10	3.10	3.30	
3"	B1	3.60	3.60	3.60		
	B2	4.10	4.00	4.10		
	A	8.25	8.25	8.25		
	B0	3.48	3.48	3.20		
			B1	3.48	3.48	3.60
			B2	4.10	4.00	4.00

- B0 Without Flush
- B1 B Dimension with 1/4 NPT Flushing Connection
- B2 B dimension with 1/2 NPT Flushing Connection



Flush Flanged Seal with Lower



Flush Flanged Seal with Lower  
 Note: 0.90 dimension is 0.70 for 4.1" Dia Diaphragm


Figure 10- Seal Dimension (Flush Flanged)

**Reference Dimensions (cont'd)**

**Flanged Seal with Extended Diaphragm**

Type	ANSI/DIN Rating	Dimension	2.8" Diaphragm Dia. (in.)	3.5" Diaphragm Dia. (in.)
Flanged Seal with Extended Diaphragm	3" Class 150#	A	7.50	-
		B	0.94	-
		C	2.80	-
	3" Class 300#	A	8.25	-
		B	1.12	-
		C	2.80	-
	DIN DN80-PN40	A	7.87	-
		B	0.94	-
		C	2.80	-
	4" Class 150#	A	-	9.00
		B	-	0.94
		C	-	3.70
4" Class 300#	A	-	10.00	
	B	-	1.25	
	C	-	3.70	
DIN DN80-PN40	A	-	9.25	
	B	-	0.94	
	C	-	3.70	


Designed to meet with schedule 40 pipe



**Figure 11 — Seal Dimensions (Extended Diaphragms)**

**Pancake Seal**


Type	ANSI/DIN	Dimension	3.5" Diaph. (in.)
Pancake Seal	Class 150#, 300#, 600# DN80-PN40	A	5.00
		B	1.08



**Figure 12 — Seal Dimensions (Pancake)**

**Chemical Tee "Taylor Wedge" Seal**

Type	Size	Dimension	3.5" Diaph. (in.)
Chemical Tee "Taylor Wedge" Seal	750 psi	A	5.00
		B	0.50



**Figure 13 — Seal Dimensions (Chemical TEE "Taylor Wedge" Seals)**

**Seal with Threaded Process Connection**

Type	Size	Dimension	2.4" Diaphragm Dia. (in.)	2.9" Diaphragm Dia. (in.)	4.1" Diaphragm Dia. (in.)
Threaded Process Conn. Seal	1/4" or 1/2"	A	3.50	4.00	5.25
		B0	1.88	1.88	1.79
		B1	1.95	1.88	1.79
	3/4" or 1"	A	3.50	4.00	5.25
		B0	1.88	1.88	1.79
		B2	2.19	2.18	2.14

- B0 Without Flush
- B1 B Dimension with 1/4 NPT Flushing Connection
- B2 B dimension with 1/2 NPT Flushing Connection




Figure 14— Seal Dimensions (Threaded Process Connection Seals)

**Sanitary Seal**

Type	Size	Dimension	1.9" Diaphragm Dia. (in.)	2.4" Diaphragm Dia. (in.)	2.9" Diaphragm Dia. (in.)	4.1" Diaphragm Dia. (in.)
Sanitary Seal	2"	A	2.50	-	-	-
		B	1.42	-	-	-
	2- 1/2"	A	-	3.00	-	-
		B	-	1.28	-	-
	3"	A	-	-	3.57	-
		B	-	-	1.38	-
	4"	A	-	-	-	4.68
		B	-	-	-	1.80




Figure 15— Seal Dimensions (Sanitary Seals)



**Saddle Seal**

Type	Size	Dimension	2.4" Diaph. (in.)
Saddle Seal	3"	A	3.50
		B	2.80
	4" or larger	A	3.50
		B	3.04

Note: Specify 6 or 8 bolt pattern




Figure 16— Seal Dimensions (3" Saddle Seal)

Type	Size	Dimension	2.4" Diaph. (in.)
Saddle Seal	3"	A	3.50
		B	2.80
	4" or larger	A	3.50
		B	3.04

Note: Specify 6 or 8 bolt pattern




Figure 17— Seal Dimensions (4" Saddle Seal)

**Calibration Ring**

Type	Size	Rating	Dimension	1/4 NPT	1/2 NPT
Calibration Ring	3"	150# / 800#	A	5.00	5.00
			B	1.00	1.50
			C	3.00	3.00




Figure 18— Calibration Ring

## Communications Protocols & Diagnostics

### HART Protocol

#### Version:

HART 7

#### Power Supply

Voltage: 10.8 to 42.4Vdc at terminals

Load: Maximum 1440 ohms. See [Figure 2](#).

Minimum Load: 0 ohms. (For handheld communications a minimum load of 250 ohms is required)

### Foundation Fieldbus (FF)

#### Power Supply Requirements

Voltage: 9.0 to 32.0Vdc at terminals

Steady State Current: 17.6mAdc

Software Download Current: 27.4mAdc

#### Available Function Blocks

Block Type	Qty	Execution Time
Resource	1	n/a
Transducer	1	n/a
Diagnostic	1	n/a
Analog Input	1*	30 ms
PID w/Autotune	1	45 ms
Integrator	1	30 ms
Signal Char (SC)	1	30 ms
LCD Display	1	n/a
Flow Block	1	30 ms
Input Selector	1	30 ms
Arithmetic	1	30 ms

\* AI block may have two (2) additional instantiations.

All available function blocks adhere to FOUNDATION Fieldbus standards. PID blocks support ideal & robust PID algorithms with full implementation of Auto-tuning.

#### Link Active Scheduler

Transmitters can perform as a backup Link Active Scheduler and take over when the host is disconnected. Acting as a LAS, the device ensures scheduled data transfers typically used for the regular, cyclic transfer of control loop data between devices on the Fieldbus.

#### Number of Devices/Segment

Entity IS model: 6 devices/segment

#### Schedule Entries

18 maximum schedule entries

#### Number of VCR's: 24 max

**Compliance Testing:** Tested according to ITK 6.0.1

### Software Download

Utilizes Class-3 of the Common Software Download procedure as per FF-883 which allows the field devices of any manufacturer to receive software upgrades from any host.

### Honeywell Digitally Enhanced (DE)

DE is a Honeywell proprietary protocol which provides digital communications between Honeywell DE enabled field devices and Hosts.

#### Power Supply

Voltage: 10.8 to 42.4Vdc at terminals

Load: Maximum 1440 ohms See [Figure 2](#).

### Standard Diagnostics

ST 700 top level diagnostics are reported as either critical or non-critical and readable via the DD/DTM tools or

#### Critical Diagnostics

HART DD/DTM tools	Basic Display
Electronic Module DAC Failure	Electronics Module fault
Meter Body NVM Corrupt	Meterbody fault
Config Data Corrupt	Electronics Module fault
Electronic Module Diag Failure	Electronics Module fault
Meter Body Critical Failure	Meterbody fault
Sensor Comm Timeout	Meterbody Comm fault

#### Non-Critical Diagnostics

HART DD/DTM tools
Display Failure
Electronic Module Comm Failure
Meter Body Excess Correct
Sensor Over Temperature
Fixed Current Mode
PV Out of Range
No Factory Calibration
No DAC Compensation
LRV Set Error – Zero Config Button
URV Set Error – Span Config Button
AO Out of Range
Loop Current Noise
Meter Body Unreliable Comm
Tamper Alarm
No DAC Calibration
Sensor Supply Voltage Low

Refer to ST 700 manuals for additional level diagnostic information

### Other Certification Options

#### Materials

- NACE MRO175, MRO103, ISO15156

**Approval Certifications:**

AGENCY	TYPE OF PROTECTION	COMM. OPTION	FIELD PARAMETERS	AMBIENT TEMP (Ta)
<b>FM Approvals™</b>	<b>Explosionproof:</b> Class I, Division 1, Groups A, B, C, D; <b>Dust Ignition Proof:</b> Class II, III, Division 1, Groups E, F, G; T4  Class I, Zone 0/1, AEx d IIC Ga/Gb T4 Class II, Zone 21, AEx tb IIIC Db T 95°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> Class I, II, III, Division 1, Groups A, B, C, D, E, F, G; T4  Class I, Zone 0, AEx ia IIC Ga T4  FISCO Field Device (Only for FF Option) Ex ia IIC T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	<b>Nonincendive:</b> Class I, Division 2, Groups A, B, C, D locations,  Class I, Zone 2, AEx nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure:</b> Type 4X/ IP66/ IP67	All	All	-
	<b>Explosion Proof:</b> Class I, Division 1, Groups A, B, C, D; <b>Dust Ignition Proof:</b> Class II, III, Division 1, Groups E, F, G; T4  Ex d IIC Ga T4 Ex tb IIIC Db T 95°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> Class I, II, III, Division 1, Groups A, B, C, D, E, F, G; T4  Ex ia IIC Ga T4  FISCO Field Device (Only for FF Option) Ex ia IIC T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
<b>Canadian Standards Association (CSA)</b>	<b>Nonincendive:</b> Class I, Division 2, Groups A, B, C, D; T4  Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure:</b> Type 4X/ IP66/ IP67	All	All	-

## Approval Certifications: (Continued)

ATEX	<b>Flameproof:</b> II 1/2 G Ex d IIC Ga/Gb T4 II 2 D Ex tb IIIC Db T 95°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> II 1 G Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	-50 °C to 70°C
	<b>Nonincendive:</b> II 3 G Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure:</b> IP66/ IP67	All	All	-
IECEX (World)	<b>Flameproof :</b> Ex d IIC Ga/Gb T4 Ex tb IIIC Db T 95°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	-50 °C to 70°C
	<b>Nonincendive:</b> Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure:</b> IP66/ IP67	All	All	-
SAEx (South Africa)	<b>Flameproof :</b> Ex d IIC Ga/Gb T4 Ex tb IIIC Db T 95°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	-50 °C to 70°C
	<b>Nonincendive:</b> Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure:</b> IP66/ IP67	All	All	-
INMETRO (Brazil)	<b>Flameproof:</b> Ex d IIC Ga/ Gb T4 Ex tb IIIC Db T 95°C	All	Note 1	T5 Ta = -50 to 93°C
	<b>Intrinsically Safe:</b> Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	T4 Ta = -50 to 93°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	T4 Ta = -50 to 70°C
	<b>Nonincendive:</b> Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure :</b> IP 66/67	All	All	-

**Approval Certifications: (Continued)**

<b>NEPSI (China)</b>	<b>Flameproof:</b> Ex d IIC Ga/Gb T4 Ex tb IIIC Db T 85°C	All	Note 1	T5 Ta = -50 to 93°C
	<b>Intrinsically Safe:</b> Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	-50 °C to 70°C
	<b>Nonincendive:</b> Ex nA IIC Gc T4	4-20 mA / DE/ HART/ Foundation Fieldbus	Note 1	-50 °C to 85°C
	<b>Enclosure :</b> IP 66/67	All	All	-
<b>GOST</b>	<b>Flameproof:</b> 1 Ex d IIC Ga/Gb T4 Ex tb IIIC Db T 85°C	All	Note 1	-50 °C to 85°C
	<b>Intrinsically Safe:</b> 0 Ex ia IIC Ga T4	4-20 mA / DE/ HART	Note 2a	-50 °C to 70°C
	FISCO Field Device (Only for FF Option) Ex ia IIC T4	Foundation Fieldbus	Note 2b	-50 °C to 70°C
	<b>Enclosure :</b> IP 66/67	All	All	

**Notes:**

## 1. Operating Parameters:

Voltage= 11 to 42 V DC      Current= 4-20 mA Normal  
= 10 to 30 V (FF)              = 30 mA (FF)

## 2. Intrinsically Safe Entity Parameters

## a. Analog/ DE/ HART Entity Values:

V<sub>max</sub>= U<sub>i</sub> = 30V      I<sub>max</sub>= I<sub>i</sub>= 105mA      C<sub>i</sub> = 4.2nF      L<sub>i</sub> =984 uH      P<sub>i</sub>=0.9W

Transmitter with Terminal Block Revision E or Later )

V<sub>max</sub>= U<sub>i</sub> = 30V      I<sub>max</sub>= I<sub>i</sub>= 225mA      C<sub>i</sub> = 4.2nF      L<sub>i</sub> = 0      P<sub>i</sub> =0.9W

Note : Transmitter with Terminal Block Revision E or later

The revision is on the label that is on the module. There will be two lines of text on the label:

- First is the Module Part #: 50049839-001 or 50049839-002
- Second line has the supplier information, along with the REVISION:  
XXXXXX-EXXXX, THE "X" is production related, THE POSITION of the "E" IS THE REVISION.

## b. Foundation Fieldbus- Entity Values

V<sub>max</sub>= U<sub>i</sub> = 30V      I<sub>max</sub>= I<sub>i</sub>= 180mA      C<sub>i</sub> = 0nF      L<sub>i</sub> = 984 uH      P<sub>i</sub> =1W

Transmitter with Terminal Block Revision F or Later )

V<sub>max</sub>= U<sub>i</sub> = 30V      I<sub>max</sub>= I<sub>i</sub>= 225mA      C<sub>i</sub> =0nF      L<sub>i</sub> = 0      P<sub>i</sub> =1 W

FISCO Field Device      I<sub>max</sub>= I<sub>i</sub>= 380 mA      C<sub>i</sub> = 0nF      L<sub>i</sub> = 0      P<sub>i</sub> =5.32 W

V<sub>max</sub>= U<sub>i</sub> = 17.5V

Note : Transmitter with Terminal Block Revision F or later

The revision is on the label that is on the module. There will be two lines of text on the label:

- First is the Module Part #: 50049839-003 or 50049839-004
- Second line has the supplier information, along with the REVISION:  
XXXXXX-EXXXX, THE "X" is production related, THE POSITION of the "E" IS THE REVISION.

**Approval Certifications: (Continued)**

<b>Marine Certificates</b>	<p>This certificate defines the certifications covered for the ST 800 Pressure Transmitter family of products, including the SMV 800 Smart Multivariable Transmitter. It represents the compilation of the five certificates Honeywell currently has covering the certification of these products into marine applications.</p> <p>For ST 800 Smart Pressure Transmitter and SMV800 Smart Multivariable Transmitter</p>
	<p><b>American Bureau of Shipping (ABS)</b> - 2009 Steel Vessel Rules 1-1-4/3.7, 4-6-2/5.15, 4-8-3/13 &amp; 13.5, 4-8-4/27.5.1, 4-9-7/13. Certificate number: 04-HS417416-PDA</p>
	<p><b>Bureau Veritas (BV)</b> - Product Code: 389:1H. Certificate number: 12660/B0 BV</p>
	<p><b>Det Norske Veritas (DNV)</b> - Location Classes: Temperature D, Humidity B, Vibration A, EMC B, Enclosure C. For salt spray exposure; enclosure of 316 SST or 2-part epoxy protection with 316 SST bolts to be applied. Certificate number: A-11476</p>
	<p><b>Korean Register of Shipping (KR)</b> - Certificate number: LOX17743-AE001</p>
	<p><b>Lloyd's Register (LR)</b> - Certificate number: 02/60001(E1) &amp; (E2)</p>
<b>SIL 2/3 Certification</b>	<p>IEC 61508 SIL 2 for non-redundant use and SIL 3 for redundant use according to EXIDA and TÜV Nord Sys Tec GmbH &amp; Co. KG under the following standards: IEC61508-1: 2010; IEC 61508-2: 2010; IEC61508-3: 2010.</p>



## Application Data

### Liquid Level: Closed Tank

Determine the minimum and maximum pressure differentials to be measured (**Figure 16**).

$$\begin{aligned} P_{\text{Min}} &= (SG_p \times a) - (SG_f \times d) \\ &= \text{LRV when HP at bottom of tank} \\ &= -\text{URV when LP at bottom of tank} \end{aligned}$$

$$\begin{aligned} P_{\text{Max}} &= (SG_p \times b) - (SG_f \times d) \\ &= \text{URV when HP at bottom of tank} \\ &= -\text{LRV when LP at bottom of tank} \end{aligned}$$

Where:

minimum level at 4mA  
maximum level at 20 mA


a = distance between bottom tap and minimum level

b = distance between bottom tap and maximum level


d = distance between taps

$SG_f$  = Specific Gravity of capillary fill fluid (See Page 6 "Material Specifications" for values.)


$SG_p$  = Specific Gravity of process fluid



Transmitter above datum



Transmitter at datum



Transmitter below datum

24253

Figure 16—Closed tank liquid level measurement distance

## Application Data (Cont'd)

### Density or Interface\*

Calculate the minimum and maximum pressure differentials to be measured (Figure 19).

$P_{\min} = (SG_{\min} - SG_f) \times (d)$ ;  
minimum density, 4mA output

$P_{\max} = (SG_{\max} - SG_f) \times (d)$ ;  
maximum density, 20mA output

Where:

$d$  = distance between the taps

$SG_{\max}$  = maximum Specific Gravity

$SG_{\min}$  = minimum Specific Gravity

$SG_f$  = Specific Gravity of capillary fill fluid (See Page 6 "Material Specifications" for values.)




Figure 19- Density, direct acting transmitter configuration

## Seal Configurations



Figure 20—Flush Flange Seals

Flush Flange Seals can be used with differential, gauge and absolute pressure transmitters and are available with 3" ANSI Class 150, ANSI Class 300 and DIN DN80-PN40 process connections. Flush flange seals can also be provided with Lowers. Lowers are essentially calibration rings, which allow flushing connections if needed.



Figure 22—Pancake Seals

Pancake Seals can be used with differential, gauge and absolute pressure transmitters and are available with 3" ANSI Class 150, 300 and 600 process connections.



Figure 21 — Flange Seal with Extended Diaphragm

Flange Seal with Extended Diaphragm can be used with differential, gauge and absolute pressure transmitters and are available with 3" and 4" ANSI Class 150, ANSI Class 300, DIN DN80-PN40 and DIN DN100-PN40 process connections. 2", 4" and 6" extension lengths are available



Figure 23— Chemical Tee "Taylor" Wedge

Chemical Tee "Taylor" Wedge can be used with differential pressure transmitters and are available with Taylor Wedge 5" O.D. process connection.

## Seal Configurations (cont'd)



**Figure 24— Seals with Threaded Process Connections**

Seals with Threaded Process Connections can be used with differential, gauge and absolute pressure transmitters and are available with ½", ¾" and 1" NPT Female process connections.



**Figure 28 — Stainless Steel Armor and PVC Coated Stainless Steel Armor Capillaries**

Stainless Steel Armor and PVC Coated Stainless Steel Armor Capillaries are available with Honeywell Remote Seal Solutions.



**Figure 25 — Sanitary Seals**

Sanitary Seals can be used with differential, gauge and absolute pressure transmitters and are available with 3" and 4" Tri-Clover-Tri-Clamp process connections.



**Figure 29 — 2" Stainless Steel Nipples**  
2" Stainless Steel Nipples are available for Close-Coupled remote seal solutions



**Figure 26— Saddle Seals**

Saddle Seals can be used with differential, gauge and absolute pressure transmitters and are available with 3" and 4" (6 bolt or 8 bolt designs) process connections.



**Figure 30 — Welded Meter Body for All-Welded Remote Seal Solution**

Welded Meter Body for All-Welded Remote Seal Solution. The welded ST 800 meter body is an important part of an All-Welded Remote Seal Solution, which is commonly used in Vacuum applications.



**Figure 27 — Calibration Rings**

Calibration Rings are available with Flush Flange Seals and Pancake Seals. Flushing ports (¼" or ½") are available with calibration rings.

## Model Selection Guide

Model Selection Guides are subject to change and are inserted into the specifications as guidance only. Prior to specifying or ordering a model check for the latest revision Model Selection Guides which are published at:

# Model STR700 (DP, GP) Remote Seals



Model Selection Guide  
34-ST-16-104 Issue 4

### Instructions

- Select the desired Key Number. The arrow to the right marks the selection available.
- Make selections from each Table (I, II and IX) using the column below the proper arrow.
- A (•) denotes unrestricted availability. A letter denotes restricted availability.
- Restrictions follow Table IX.

Key Number	I	II	III	IV	V	VI	VII	VIII	IX
STR7	---	---	---	---	---	---	---	---	0000

KEY NUMBER	URL	LRL	Max Span	Min Span	Units	Selection	Availability
Measurement Range Std Accuracy	100 (7)	-100 (-7)	100 (7)	1 (0.07)	psi (bar)	STR73D	↓
	500 (35)	-9 (-0.62)	500 (35)	5 (0.35)	psi (bar)	STR74G	↓

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.

TABLE I	Description		Selection			
Meter Body & Capillaries	a. Number of Seals	1 Remote Seal (High Side)	1	•	•	
		2 Remote Seals	2	•	•	
		1 Remote Seal (Low Side)	3	•	•	
	b. Primary Fill Fluid	Silicone Oil 200	1	•	•	
		Fluorinated Oil CTFE	2	2	2	
	c. Construction	<b>Non-Wetted Adapter Head Materials</b>				
	In-Line Gauge	316 SS Bonnet		A	•	
		316 SS Bonnet for Close-Couple		B		3
		316 SS (bolt-on heads)		C	•	
	Dual Head DP	316 SS for Close-Couple		D	3	
		316 SS with all-welded meter body		E	4	
		None		0	22	•
	d. Bolts and Nuts for Transmitter Heads	Carbon Steel Bolts and Nuts		C	•	
		316 SS Bolts and Nuts		S	•	
		A286 SS (NACE) Bolts and 304 SS (NACE) Nuts		N	•	
		B7M (NACE) Bolts and 7M (NACE) Nuts		B	•	
		None		0	5	5
e. Secondary Fill Fluid (capillary & seal)	Silicone Oil 200		1	•	•	
	Fluorinated Oil CTFE		2	•	•	
	Silicone Oil704		3	•	•	
	Neobee® M20 <sup>11</sup>		4	•	•	
	Syltherm® 800 <sup>12</sup>		5	•	•	
	No Capillary, No Nipple (Specify for VAM Unit Only)		0	5	5	
f. Connection of Remote Seal to Meter Body	Capillary Length	5 feet 1.5 m	A	•	•	
		10 feet 3.0 m	B	•	•	
		15 feet 4.5 m	C	•	•	
		20 feet 6.1 m	D	•	•	
		25 feet 7.5 m	E	•	•	
		35 feet 10.7 m	F	•	•	
	Capillary Length	5 feet 1.5 m	G	•	•	
		10 feet 3.0 m	H	•	•	
		15 feet 4.5 m	J	•	•	
		20 feet 6.1 m	K	•	•	
		25 feet 7.5 m	L	•	•	
		35 feet 10.7 m	M	•	•	
2 inch long SS nipple close-coupled		2	6	6		
g. Seal Option	None		0	•	•	
	Std Gold Plated Seal Diaph. = 50 µin		1	7	7	
	Teflon Coated Seal Diaphragm - only for anti-sticking		4	7	7	

<sup>11</sup> Limited vacuum availability.

<sup>12</sup> Minimum static pressure requirement. No vacuum allowed. See Specifications 34-ST-03-88 Figure 15




In-Line Gauge



Dual Head DP



All welded



**Note:** When selecting required seal, you must specify only the 9 selections within the required seal type.


TABLE II		Description			Selection			
<b>Seals</b>	No Seal Attached to Core Transmitter (Specify for VAM Unit Only)				0 0 0 0 0 0 0 0 0	21	21	
	 Flush Flanged Seal	Seal Type	Diaphragm Diameter	Flange Size	Flange Pressure Rating <sup>1</sup>	Selection		
			3.5"	3"	ANSI Class 150 ANSI Class 300	AFA _____ AFC _____	•	•
				80mm	DIN DN80-PN40	AFM _____	•	•
			Wetted Material	Diaphragm      Upper Insert		Selection		
				316L SS	316L SS	___ AA ___	•	•
				Hastelloy® C-276	316L SS	___ AB ___	•	•
				Hastelloy® C-276	Hastelloy® C-276	___ AC ___	•	•
				Monel 400®	Monel 400®	___ AE ___	8	8
				Tantalum <sup>5</sup>	316L SS	___ AF ___	8	8
			Non-Wetted Material (upper)	CS (Nickel Plated) 316L SS		___ 1 ___ ___ 2 ___	•	•
			Seal-Capillary Connection	Center Seal Side Seal		___ 1 ___ ___ 2 ___	•	•
			Calibration Rings	None 316L SS Hastelloy® C-276 Monel 400®		___ A ___ ___ B ___ ___ C ___ ___ D ___	•	•
			Flushing Connections and Plugs <sup>4</sup> (Metal plug material will be the same as Cal. ring material if metal plug is chosen )	None One 1/4" with plastic plug One 1/4" with metal plug Two 1/4" with plastic plugs Two 1/4" with metal plugs One 1/2" with plastic plug One 1/2" with metal plug Two 1/2" with plastic plugs Two 1/2" with metal plugs		___ 0 ___ ___ H ___ ___ J ___ ___ M ___ ___ N ___ ___ P ___ ___ Q ___ ___ R ___ ___ S ___	•	•

Table II continued next page

<sup>1</sup> Standard facing 125-250 AARH RF (raised face) serrated surface finish.  
<sup>4</sup> Plastic Plugs are TEMPORARY ONLY to protect threads and MUST be REMOVED before installation  
<sup>5</sup> Tantalum Upper insert has Tantalum wetted parts and 316 SS or CS non-wetted parts

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.

STR74G  
STR73D


TABLE II		Description				Selection			
Seal Type	Diaphragm Diameter	Flange Size	Flange Pressure Rating <sup>1</sup>	Const. - See Spec. Figure 34-ST-03-104	Construction - See Spec. Figure 34-ST-03-104				
Seals (continued)		2.4"	1"	ANSI 150	22	BCA _____	12	•	
				ANSI 300	22	BCC _____	12	•	
			1-1/2"	ANSI 150	22	BGA _____	12	•	
				ANSI 300	22	BGC _____	12	•	
			2"	ANSI 150	22	BDA _____	12	•	
				ANSI 300	22	BDC _____	12	•	
			3"	ANSI 150	22	BFA _____	12	•	
				ANSI 300	22	BFC _____	12	•	
		2.9"	1/2"	ANSI 150	23	CAA _____	•	•	
			1"	ANSI 150	23	CCA _____	•	•	
				ANSI 300	23	CCC _____	•	•	
			1-1/2"	ANSI 150	22	CGA _____	•	•	
				ANSI 300	22	CGC _____	•	•	
			2"	ANSI 150	22	CDA _____	•	•	
				ANSI 300	22	CDC _____	•	•	
		4.1"	1/2"	ANSI 150	22	DAA _____	•	•	
			1"	ANSI 150	23	DCA _____	•	•	
				ANSI 300	23	DCC _____	•	•	
			1-1/2"	ANSI 150	23	DGA _____	•	•	
				ANSI 300	23	DGC _____	•	•	
			2"	ANSI 150	23	DDA _____	•	•	
				ANSI 300	22	DDC _____	•	•	
		Wetted Material	Diaphragm		Lower		Selection		
			316L SS		316L SS		BA _____	•	•
			Hastelloy® C-276		316L SS		BB _____	•	•
			Hastelloy® C-276		Hastelloy® C-276		BC _____	•	•
			Monel 400®		Monel 400®		BE _____	8	8
			Tantalum		316L SS		BF _____	8	8
			Tantalum		Hastelloy® C-276		BG _____	8	8
		Tantalum		Tantalum Clad		BH _____	13	13	
Non-Wetted Material (upper, upper insert)	Upper		Upper Insert		Selection				
	316L SS		316L SS		4 _____	•	•		
Carbon Steel		316L SS		5 _____	•	•			
Bolts <sup>ε</sup>		No Selection			0 _____	•	•		
Flushing		None			0 _____	•	•		
Connections and Plugs <sup>4</sup> (Metal plug material will be the same as Lower material, if metal plug is chosen - (SS Plug for CS Lower and Tantalum Clad)	One 1/4" with plastic plug				H _____	•	•		
	One 1/4" with metal plug				J _____	•	•		
	Two 1/4" with plastic plugs				M _____	•	•		
	Two 1/4" with metal plugs				N _____	•	•		
	One 1/2" with plastic plug				P _____	•	•		
	One 1/2" with metal plug				Q _____	•	•		
	Two 1/2" with plastic plugs				R _____	•	•		
Two 1/2" with metal plugs				S _____	•	•			
Gasket	Klinger® C-4401 (non-asbestos)				K _____	•	•		
	Grafoil®				G _____	•	•		
	Teflon®				T _____	•	•		
	Gylon® 3510				L _____	15	15		

Table II continued next page

<sup>1</sup> Standard facing 125-250 AARH RF (raised face) serrated surface finish.

<sup>6</sup> Bolt material will be same as Upper Material. However, if Table I bolts/nuts material is NACE or B7M, seal bolt material will be 304 SS NACE.

<sup>4</sup> Plastic Plugs are TEMPORARY ONLY to protect threads and MUST be REMOVED before installation

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.



STR74G  
STR73D


TABLE II	Description							
Seal Type	Diaphragm Diameter	Flange Size	Flange Pressure Rating <sup>1</sup>		Selection			
 Flange Seal with Extended Diaphragm	2.8"	3" (2.8" OD extension)	ANSI Class 150		EFA _____	•	•	
			ANSI Class 300		EFC _____	•	•	
	DIN DN80-PN40				EFM _____	•	•	
	3.5"	4" (3.70" OD extension)	ANSI Class 150		FGA _____	•	•	
			ANSI Class 300		FGC _____	•	•	
			DIN DN100-PN40		FGP _____	•	•	
	Wetted Material	Diaphragm		Ext. Tube	Selection			
		316L SS		316L SS	EA _____	•	•	
	Hastelloy® C-276		316L SS		EB _____	•	•	
	Hastelloy® C-276		Hastelloy® C-276		EC _____	•	•	
Non-Wetted Material (flange)		CS (Nickel Plated)		_____ 7 _____	•	•		
Bolts		No Selection		_____ 8 _____	•	•		
Extension Length		2"		_____ 0 _____	•	•		
		4"		_____ 2 _____	•	•		
		6"		_____ 4 _____	•	•		
				_____ 6 _____	•	•		
No Selection	No Selection	No Selection		_____ 0 _____	•	•		

Table II continued below

STR74G  
STR73D


TABLE II	Description							
Seal Type	Diaphragm Diameter	Flange Size	Flange Pressure Rating Dependent on Customer Flange <sup>1</sup>		Selection			
 Pancake Seal	3.5"	3"	ANSI Class 150/300/600		GFA _____	•	•	
			Diaphragm		Body			
	Wetted Material		316L SS		316L SS	GA _____	•	•
	Hastelloy® C-276		Hastelloy® C-276		Hastelloy® C-276	GB _____	•	•
	Monel 400®		Monel 400®		Monel 400®	GC _____	•	•
	Tantalum		Tantalum <sup>7</sup>		Tantalum	GE _____	8	8
						GG _____	8	8
	Non-Wetted Material		No Selection		_____ 0 _____	•	•	
	Bolts		No Selection		_____ 0 _____	•	•	
	Calibration Rings		None		_____ A _____	•	•	
		316L SS		_____ B _____	10	10		
		Hastelloy® C-276		_____ C _____	10	10		
		Monel 400®		_____ D _____	10	10		
Flushing Connections and Plugs <sup>4</sup> (Metal plug material will be the same as Cal. Ring material, if metal plug is chosen)		None		_____ 0 _____	•	•		
		One 1/4" with plastic plug		_____ H _____	11	11		
		One 1/4" with metal plug		_____ J _____	11	11		
		Two 1/4" with plastic plugs		_____ M _____	11	11		
		Two 1/4" with metal plugs		_____ N _____	11	11		
		One 1/2" with plastic plug		_____ P _____	11	11		
		One 1/2" with metal plug		_____ Q _____	11	11		
		Two 1/2" with plastic plugs		_____ R _____	11	11		
		Two 1/2" with metal plugs		_____ S _____	11	11		

Table II continued next page

<sup>1</sup> Standard facing 125-250 AARH RF (raised face) serrated surface finish.

<sup>4</sup> Plastic Plugs are TEMPORARY ONLY to protect threads and MUST be REMOVED before installation

<sup>7</sup> Tantalum Body has Tantalum wetted parts and 316 SS non-wetted parts

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.

STR74G  
STR73D


TABLE II		Description				
Seal Type	Diaphragm Diameter	Flange Size	Flange Pressure Rating <sup>1</sup>		Selection	
 Chemical Tee "Taylor" Wedge	3.5"	Taylor Wedge 5" O.D.	750 psi		HM0 _____ 16	
	Wetted Material		Diaphragm	Body	Selection	
			316L SS	316L SS	HA _____ •	
			Hastelloy® C-276	316L SS	HB _____ •	
			Hastelloy® C-276	Hastelloy® C-276	HC _____ •	
	Non-Wetted Material		No Selection		_____ 0 _____ •	
	Bolts		No Selection		_____ 0 _____ •	
Styles		No Selection		_____ 0 _____ •		
No Selection		No Selection		_____ 0 _____ •		

Table II continued below


TABLE II		Description				
Seal Type	Diaphragm Diameter	Threaded Process Connection Size (NPT Female)	Pressure Rating		Selection	
			CS Bolts	304 SS Bolts		
 Seal with Threaded Process Connection	2.4"	1/2 NPT	2,500 psi	1,250 psi	JJG _____ 12 •	
		3/4 NPT			JKG _____ 12 •	
		1 NPT			JLG _____ 12 •	
	2.9"	1/2 NPT	2,500 psi	1,250 psi	KJG _____ • •	
		3/4 NPT			KKG _____ • •	
		1 NPT			KLK _____ • •	
	4.1"	1/2 NPT	1,500 psi	750 psi	LJG _____ • •	
		3/4 NPT			LKG _____ • •	
		1 NPT			LLG _____ • •	
	Wetted Material		Diaphragm	Lower	Selection	
			316L SS	Carbon Steel	JA _____ • •	
			316L SS	316L SS	JB _____ • •	
			Hastelloy® C-276	316L SS	JC _____ • •	
			Hastelloy® C-276	Hastelloy® C-276	JD _____ • •	
			Monel 400®	Monel 400®	JE _____ 8 8	
			Tantalum	316L SS	JF _____ 8 8	
			Tantalum	Hastelloy® C-276	JG _____ 8 8	
Non-Wetted Material (upper)		CS (Nickel Plated)		_____ A _____ • •		
		316 Stainless Steel		_____ C _____ 17 17		
Bolts <sup>2</sup>		Carbon Steel		_____ C _____ • •		
		304 SS		_____ D _____ • •		
Flushing Connections and Plugs <sup>4</sup>		None		_____ 0 _____ • •		
(Metal plug material will be the same as Lower material, if metal plug is chosen - (SS Plug for CS Lower and Tantalum Clad))		One 1/4" with plastic plug		_____ H _____ • •		
		One 1/4" with metal plug		_____ J _____ • •		
		Two 1/4" with plastic plugs		_____ M _____ • •		
		Two 1/4" with metal plugs		_____ N _____ • •		
		One 1/2" with plastic plug		_____ P _____ 18 18		
		One 1/2" with metal plug		_____ Q _____ 18 18		
		Two 1/2" with plastic plugs		_____ R _____ 18 18		
		Two 1/2" with metal plugs		_____ S _____ 18 18		
Gasket		Klinger® C-4401 (non-asbestos)		_____ K _____ • •		
		Grafoil®		_____ G _____ • •		
		Teflon®		_____ T _____ • •		
		Gylon® 3510		_____ L _____ 15 15		

Table II continued next page

<sup>1</sup> Standard facing 125-250 AARH RF (raised face) serrated surface finish.

<sup>4</sup> Plastic Plugs are TEMPORARY ONLY to protect threads and MUST be REMOVED before installation

<sup>2</sup> If Table I Bolts and Nuts material option is NACE, Bolts and Nuts will ship with Alloy Steel NACE and MAWP may change.

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.

STR74G  
STR73D



TABLE II		Description						
Seals (continued)	Seal Type	Diaphragm Diameter	Flange Size	Pressure Rating		Selection		
		1.9"	2"	Customer clamp rating or 600 psi, whichever is less		MD0 _____	19	
		2.4"	2-1/2"			NE0 _____	20 19	
		2.9"	3"			PF0 _____	19 19	
		4.1"	4"			QG0 _____	19 19	
	Sanitary Seal <sup>9</sup>	Wetted Material		Diaphragm	Body	Selection		
				316L SS	316L SS	___ NA ___	• •	
	Non-Wetted Material		No Selection		_____ 0 _____		• •	
	Bolts		No Selection		_____ 0 _____		• •	
Styles		Tri-Clover Tri-Clamp®		_____ 8 _____		• •		
Gasket		No Selection		_____ 0 _____		• •		

Table II continued below

STR74G  
STR73D

TABLE II		Description							
Seals (continued)	Seal Type	Diaphragm Diameter	Size and Bolt Pattern	Seal Pressure Rating		Selection			
				C.S. Bolts	304 SS Bolts				
		8-Bolt Design	2.4"	for 3" Pipe ≥ 4" pipe	2,500 psi	1,250 psi	RFK _____	12 •	
							RGK _____	12 •	
		6-Bolt Design	2.4"	for 3" Pipe ≥ 4" pipe	2,000 psi	1,000 psi	RPK _____	12 •	
							RQK _____	12 •	
		Wetted Material	Diaphragm		Lower Housing		Selection		
			316L SS		Carbon Steel		___ RA ___		• •
			316L SS		316L SS		___ RB ___		• •
			Hastelloy® C-276		316L SS		___ RC ___		• •
Hastelloy® C-276			Hastelloy® C-276		___ RD ___		• •		
316L SS			NA-Body Only <sup>10</sup>		___ SB ___		• •		
Hastelloy® C-276		NA-Body Only <sup>10</sup>		___ SC ___		• •			
Non-Wetted Material	Body		Bolts <sup>10,11</sup>		Selection				
	Carbon Steel		Carbon Steel		_____ B _____		8 8		
316L SS		316 SS		_____ C _____		• •			
Bolts		No Selection		_____ 0 _____		• •			
Styles		No Selection		_____ 0 _____		• •			
Gasket		Klinger® C-4401 (non-asbestos)		_____ K _____		• •			
		Grafoil®		_____ G _____		• •			
		Teflon®		_____ T _____		• •			
		Gylon® 3510		_____ L _____		• •			

<sup>9</sup> All sanitary seals have dairy grade 3A approval.

<sup>10</sup> Bolts are not included with "body only" selection.

<sup>11</sup> If Table I Bolts and Nuts material option is NACE, seal bolt material will be 304 SS NACE.

Note: Remote seal system pressure rating is body rating or seal rating, whichever is less.



TABLE III Agency Approvals (see data sheet for Approval Code Details)	
Approvals	No Approvals Required
	FM Explosion proof, Intrinsically Safe, Non-incendive, & Dustproof
	CSA Explosion proof, Intrinsically Safe, Non-incendive, & Dustproof
	ATEX Explosion proof, Intrinsically Safe & Non-incendive
	IECEX Explosion proof, Intrinsically Safe & Non-incendive
	SAEx/CCoE Explosion proof, Intrinsically Safe & Non-incendive
	INMETRO Explosion proof, Intrinsically Safe & Non-incendive
NEPSI Explosion proof, Intrinsically Safe & Non-incendive	




TABLE IV TRANSMITTER ELECTRONIC SELECTIONS			
a. Electronic Housing Material & Connection Type	Material	Connection	Lightning Protection
	Polyester Powder Coated Aluminum	1/2 NPT	None
	Polyester Powder Coated Aluminum	M20	None
	Polyester Powder Coated Aluminum	1/2 NPT	Yes
	Polyester Powder Coated Aluminum	M20	Yes
	316 Stainless Steel (Grade CF8M)	1/2 NPT	None
	316 Stainless Steel (Grade CF8M)	M20	None
	316 Stainless Steel (Grade CF8M)	1/2 NPT	Yes
	316 Stainless Steel (Grade CF8M)	M20	Yes
b. Output/ Protocol	Analog Output		Digital Protocol
	4-20mA dc		HART Protocol
	4-20mA dc none		DE Protocol Foundation Fieldbus
c. Customer Interface Selections	Indicator	Ext Zero, Span & Config Buttons	Languages
	None	None	None
	None	Yes (Zero/Span Only)	None
	Basic	None	English
	Basic	Yes	English





TABLE V CONFIGURATION SELECTIONS			
a. Application Software	Diagnostics		
	Standard Diagnostics		
b. Output Limit, Failsafe & Write Protect Settings	Write Protect	Fail Mode	High & Low Output Limits <sup>3</sup>
	Disabled	High > 21.0mA dc	Honeywell Std (3.8 - 20.8 mA dc)
	Disabled	Low < 3.6mA dc	Honeywell Std (3.8 - 20.8 mA dc)
	Enabled	High > 21.0mA dc	Honeywell Std (3.8 - 20.8 mA dc)
	Enabled	Low < 3.6mA dc	Honeywell Std (3.8 - 20.8 mA dc)
	Enabled	N/A	N/A Fieldbus
	Disabled	N/A	N/A Fieldbus
c. General Configuration	Factory Standard		
	Custom Configuration (Unit Data Required from customer)		






TABLE VI CALIBRATION & ACCURACY SELECTIONS			
Accuracy and Calibration	Accuracy	Calibrated Range	Calibration Qty
	NA	None	None
	Standard	Factory Std	Single Calibration
	Standard	Custom (Unit Data Required)	Single Calibration



<sup>3</sup> NAMUR Output Limits 3.8 - 20.5mA dc can be configured by the customer or select custom configuration Table Vc




TABLE VII		ACCESSORY SELECTIONS	
a. Mounting Bracket	Bracket Type	Material	
	None	None	
	Angle Bracket	Carbon Steel	
	Angle Bracket	304 SS	
	Angle Bracket	316 SS	
	Marine Approved Angle Bracket	304 SS	
	Flat Bracket	Carbon Steel	
	Flat Bracket	304 SS	
b. Customer Tag	Customer Tag Type		
	No customer tag		
	One Wired Stainless Steel Tag (Up to 4 lines 26 char/line) Two Wired Stainless Steel Tag (Up to 4 lines 26 char/line)		
c. Unassembled Conduit Plugs & Adapters	Unassembled Conduit Plugs & Adapters		
	No Conduit Plugs or Adapters Required		
	1/2 NPT Male to 3/4 NPT Female 316 SS Certified Conduit Adapter		
	1/2 NPT 316 SS Certified Conduit Plug		
	M20 316 SS Certified Conduit Plug		
	Minifast® 4 pin (1/2 NPT) Minifast® 4 pin (M20)		

0	---	•	•
1	---	•	•
2	---	•	•
3	---	•	•
4	---	y	•
5	---	•	•
6	---	•	•
7	---	•	•

0	---	•	•
1	---	•	•
2	---	•	•

--	A0	•	•
--	A2	n	n
--	A6	n	n
--	A7	m	m
--	A8	n	n
--	A9	m	m

TABLE VIII		OTHER Certifications & Options : (String in sequence comma delimited (XX, XX, XX,...))
Certifications & Warranty	None - No other options	
	NACE MR0175; MR0103; ISO15156 (FC33338) Process wetted parts only	
	NACE MR0175; MR0103; ISO15156 (FC33339) wetted and non-wetted parts	
	Marine (DNV, ABS, BV, KR, LR) (FC33340)	
	EN10204 Type 3.1 Material Traceability (FC33341)	
	Certificate of Conformance (F3391)	
	Calibration Test Report & Certificate of Conformance (F3399)	
	Certificate of Origin (F0195)	
	FMEDA (SIL 2/3) Certification (FC33337)	
	Over-Pressure Leak Test Certificate (1.5X MAWP) (F3392) Cert Clean for O <sub>2</sub> or CL <sub>2</sub> service per ASME G93	

00	*	*	
FG	•	•	b
F7	c	c	
MT	d	d	
FX	•	•	
F3	•	•	b
F1	•	•	
F5	•	•	
FE	i	i	
TP	•	•	
OX	e	e	

TABLE IX		Manufacturing Specials
Factory	Factory Identification	

0000	•	•
------	---	---

**MODEL RESTRICTIONS**

Restriction Letter	Available Only With		Not Available With	
	Table	Selection(s)	Table	Selection(s)
<b>b</b>	Select only one option from this group			
<b>d</b>			Vila	1,2,3,5,6,7 ___
<b>c</b>	ld	___ 0, N, B ___		
<b>e</b>	lb	___ 2 ___		
<b>f</b>			IVb	___ F ___
<b>g</b>			IVb	___ H, D ___
<b>j</b>	IVb	___ H ___	Vb	___ 1,2,6 ___
<b>m</b>	IVa	B, D, F, H ___		
<b>n</b>	IVa	A, C, E, G ___		
<b>y</b>			lc	___ E ___
<b>2</b>	le	___ 0 ___ ___ 2 ___ ___ 4 ___		
<b>3</b>	lf	___ 2 ___	la	___ 2 ___
<b>4</b>	l	___ 2 ___ 0 ___		
<b>5</b>	VI	___ 0 ___		
<b>6</b>	l	___ B, D ___	VIII la	FG, F7, FX, OX, TP, MT, F1 ___ 2 ___
<b>7</b>			II	AF BF BG BH GG JF JG
<b>8</b>			VIII	FG, F7
<b>9</b>	II	___ AA2 ___ ___ AB2 ___		
<b>10</b>			II	___ 0 ___
<b>11</b>			II	___ A ___
<b>12</b>	lf	___ A, G, 2 ___		
<b>13</b>	II	___ 0 ___	II VIII	___ T ___ FG, F7
<b>15</b>	II	___ BF ___ ___ BG ___ ___ BH ___ ___ JF ___ ___ JG ___		
<b>16</b>	l	___ 2 ___		
<b>17</b>			II	___ JA ___
<b>18</b>			II	JJG JKG JLG
<b>19</b>			la lf	___ 2 ___ ___ 2 ___
<b>20</b>	lf	___ A, G, 2 ___		
<b>21</b>	l	___ 000 ___		
<b>22</b>	lc	___ E ___		

FM Approvals<sup>SM</sup> is a service mark of FM Global  
 Hastelloy<sup>®</sup> is a registered trademark of Haynes International  
 Monel 400<sup>®</sup> is a registered trademark of Special Metals Corporation.  
 HART<sup>®</sup> is a registered trademark of HART Communication Foundation.  
 FOUNDATION<sup>™</sup> Fieldbus is a registered trademark of Fieldbus Foundation.  
 Teflon<sup>®</sup> is a registered trademark of DuPont.  
 Neobee<sup>®</sup> is a registered trademark of Stepan Company.  
 Syltherm<sup>®</sup> 800 is a Trademark of Dow Corning Corporation  
 Klinger<sup>®</sup> C-4401 is a registered trademark of THERMOSEAL, INC  
 GRAFOIL<sup>®</sup> is a registered trademarks of GrafTech International Holdings Inc  
 Gylon<sup>®</sup> 3510 is registered trademark of Garlock Sealing Technologies  
 Tri-Clover Tri-Clamp<sup>®</sup> is a registered trademark of Alfa-Laval



По вопросам продаж и поддержки обращайтесь:

Астана +7(7172)727-132, Волгоград (844)278-03-48, Воронеж (473)204-51-73, Екатеринбург (343)384-55-89, Казань (843)206-01-48,  
Краснодар (861)203-40-90, Красноярск (391)204-63-61, Москва (495)268-04-70, Нижний Новгород (831)429-08-12, Новосибирск (383)227-86-73,  
Ростов-на-Дону (863)308-18-15, Самара (846)206-03-16, Санкт-Петербург (812)309-46-40, Саратов (845)249-38-78, Уфа (347)229-48-12

Единый адрес: [hwn@nt-rt.ru](mailto:hwn@nt-rt.ru)

[www.honeywell.nt-rt.ru](http://www.honeywell.nt-rt.ru)

---